

液化石油气LPG加气机

LPGDispenser

CE APPROVAL



液化石油气LPG加气机 LPG Dispenser

Welldone 汇洋能源



LPG加气机可选配容积式流量计和质量流量计

LPG Dispenser Can Inside Piston Flowmeter OR Mass Flowmeter (Can Be Chosen)



Piston Meter
容积式流量计



Mass KG Meter ATEX Approval
质量流量计ATEX 认证

产品功能 Product Features

电脑控制, 电子计控装置能自动显示加气量和加气金额.

当加满气时, 具有自动停机功能; 超时不加气也能自动停机, 可设定大小流速保护.

可以复显最近10次的加气数据, 以备查验.

具有自动检测故障功能, 能自动显示故障代码.

可以配备后台管理系统及IC卡操作系统, 使加气站实现自动化管理.

具有拉断保护功能, 保证汽车意外拖走加气枪时安全脱离并密封.

可带GPRS功能和手机联网

可带太阳能功能

Automatic temperature compensation function

Electronic Calibration.

Fueling times limit.

Can add solar power function

Can set the decimal point for the display, so can be used in many country with different currency rate.

Leaves the communication ports, so it can communicate with the gas station management system.

Can add GPRS function , connect with mobile phone to check data and set unit price anytime anywhere

Can do OEM as required

具有定金额、定加气量的预置加气功能.

断电后数据长期保存, 并具有停电复显功能.

可以统计当班加气累计数值和汇总累计数值.

具有与其他设备通讯的能力, 通讯方式有多种可选.

能对不同形式接口的燃气汽车进行加气.

可带多媒体

可带触摸屏

可接受定制

Automatic proportion adjust for butane and propane.

Printer(option)

Stop fueling by integer sale.

Screen touch

主要技术参数 Technical Specification

测量精度 Measurement Precision	±0.5%
重复性误差 Repeatability Error	≤0.5%
计量单位 Unit Of Measurement	加气量: 升或kg
金额 Amount	元
单价 Unit Price	元/L
单次范围 Single Range	(1-9900.00) L或元
累计量程 Cumulative Range	(1-99999999.99) L或元
密度预设范围 Density Preset Range	0.5000~0.6999
充气预设范围 Gas-filling Preset Range	0.3~9000L
单价范围 Unit Price Range	0~9999,0~999999 (可变)
单程 Single Range	1~999.99,1~999999.99 (可变)
累计范围 Accumulative Range	0~9999999999.99
额定工作压力 Rated Working Pressure	2.2MPa
最小被测量 Minimum Measurand	2.5kg或5L
环境温度适应性 Ambient Temperature	-40°C ~ +55°C
相对湿度适应性 Humidity	30%~90%
大气压力 Air Pressure	86kPa~106kPa
电源适应能力 Power	AC220V(+10%,-15%), (50±1)Hz
额定功率 Rating Power	<100W
流量 Flow Rate	45L/Min
枪数 Nozzle No.	1or2可定制can do OEM
流量计类型 Floumeter type	容积式或质量流量计 Piston or mass meter

备注: 如果选择质量流量计可以计量升, 加仑, 质量, 公斤

Remark: If choose mass meter, It can , measure liter gallon mass , kg, at the same time

液化石油气LPG加气机 LPG Dispenser


Welldone 汇洋能源

LPG撬装 LPG filling skid WDLPG-T

可接受定制 Can do OEM.

请提供所需设备规格, 罐子大小要求, 以便报价.

Please issue LPG filling skid details , as LPG tank capacity, specification and so on, So to supply best suggestion.



LPG 车载撬装 LPG Mini Skid (如果需要其他配置请说明 Other specification ,please notify when order)

可以选配拉绳器和管子 Hose reel and hose optional

可以选配加气枪 Nozzle optional

可带GPRS功能和手机联网 Can add GPRS function , connect with mobile phone to check data and set unit price anytime anywhere

可接受定制 Can do OEM as required

内部是质量流量计, 可以计量升, 加仑, 质量, 公斤. Itside mass meter can measure liter , gallon mass, kg at the same time.



WD-LPGMI



质量流量计 (ATEX认证) Coriolis Mass Meter Inside (ATEX Approval)

主要技术参数 Technical Specification

质量精度 Mass Accuracy	$\pm 0.2\%$
温度精度 Temp.Accuracy	$\pm 1^{\circ}\text{C}$
重复性 Repeatability	0.1%
湿度 Humidity	30%~90%
空气压力 Air pressure	86~106KPa
电压 Power	DC 12V/24V or AC110V/220V
精度 Measurement precision	$\pm 0.2\%$
压力 Pressure	0-4MPa
连接方式 End connection	Flange/ 法兰 or Thread/ 螺纹
最大流量 Max.flow rate	12000KG/H Stainless steel material/ 不锈钢材质

液化石油气LPG加气机 LPG Dispenser

Welldone 汇洋能源

液化石油气小型撬装装置安装在液化石油气罐车上,用于装卸液化石油气。

内部配备科里奥利质量流量计(精度高,即便在不同高度、温度或环境下也不会影响任何精度,它能够按质量进行测量,可同时显示4种单位,即升、加仑、质量、千克)。

LPG Mini Skid Install on the LPG tanktruck ,loading and unloading LPG.

Coriolis Mass Meter Inside (high accuracy ,will not affect anyaccuracy even in different height or temperature or environment ,it can measureby mass,Itcan show 4 units at the same time as: liter,gallon,mass,kg)



LPGM3

主要技术参数 Technical Specification

质量精度 Mass Accuracy	±0.2%
温度精度 Temp.Accuracy	±1°C
重复性 Repeatability	0.1%
湿度 Humidity	30%~90%
气压 Air pressure	86~106KPa
电源 Power	DC 12V/24V or AC110V/220V
测量精度 Measurement precision	±0.2%
压力 Pressure	0-4MPa
端部连接 End connection	Flange or Thread
最大流量 Max.flow rate	12000KG/H

不锈钢材质, 卷管器和软管可按需选配, 喷嘴可按需选配(如需其他规格, 请在订购时告知)。

Stainless steel material , Hose reel and hose optional, Nozzle optional (Other specification ,please notify when order)



WDCZLPG

主要技术参数 Technical Specification

精确度等级 Mass accuracy grade	0.2 0.3 0.5 可选择choose
温度测量精度 Remp.accuracy	±1°C
重复性 Repeatability	±0.05%
最大工作压力 Mpa	4MPa
口径 Nomianal diameter	50mm
连接端口End connection	法兰. (可定制) Flange (customizable) M32×1.5螺母 (可定制) M32×1.5Nut (customized)
流体温度 Fluid temperature	-200~200°C
测量管材料 Wetted parts	不锈钢Stainless steel 316L
相对湿度 RH	=95%, non condensed
压损 Loss of pressure	=0.2MPa
防爆等级 Ex-mark	Ex II 2G Ex db [ib] IIC T6... T1 Gb(Transmitter) Ex ib IIC T6...T1 Gb(Sensor)
工作电压 Operating voltage	AC85~265V, DC24V
输出信号 Output signal	RS485 ; Modbus RTU ; 0~10KHz 瞬间流量脉冲信号 Sight flow pulse signal

液化石油气LPG加气机 LPG Dispenser

Welldone 汇洋能源

移动式液化气加气机 LPG Mobile Dispenser



可带GPRS功能和手机联网

如需配上LPG罐, 请告知LPG储罐容积大小或客户自行安装LPG储罐

可接受定制

Can add GPRS function , connect with mobile phone to check data and set unit price anytime anywhere

If need add LPG tank, please inform the LPG tank capacity or customer can add themselves.

Can do OEM as required

主要技术参数 Technical Specification

流量 Flow Rate	50L/min
工作压力 Working Pressure	1.8Mpa
精度 Accuracy	±0.3%
真空度 Vacuum	≥0.035MPa
总累 Totalizer	8digital
加气量 Sub-total	5digital
环境温度 Temperature	-40~55℃
流量计 Flowmeter	容积流量计 Piston meter LPG
泵 Pump	LPG泵 LPG pump
过滤分离器 Filter Separator	LPG 分离器 LPG Separator
电源 Power	AC380V±20%50±1Hz , AC220V±20%50±1Hz
防爆电机 Explosion-proof motors	380V,50Hz 4Kw , 220V,50Hz 4Kw
出气管 Hose	3/4" 500mm可接受定制 Can do OEM as required
进气管 Connection	法兰 Flange
脱落阀 Breakaway	带 yes

液化石油气LPG加气机 LPG Dispenser

Welldone 汇洋能源

LPG电脑控制器 LPG Dispenser Electronic Controller Set



产品功能 Product Features

电脑控制, 电子计控装置能自动显示加气量和加气金额。
加满气或超时不加气时自动停机, 可设定大小流速保护。
可以复显最近10次的加气数据, 以备查验。
具有自动检测故障功能, 能自动显示故障代码。

Automatic temperature compensation function

Electronic Calibration.

Fueling times limit.

Can add solar power function

Can set the decimal point for the display, so can be used in many country with different currency rate.

Leaves the communication ports, so it can communicate with the gas station management system.

Can add GPRS function , connect with mobile phone to check data and set unit price anytime anywhere

Can do OEM as required

可以配备后台管理系统及IC卡操作系统, 使加气站实现自动化管理。
具有拉断保护功能, 保证汽车意外拖走加气枪时安全脱离并密封。
可带GPRS功能和手机联网
可带太阳能功能

Automatic proportion adjust for butane and propane.

Printer(option)

Stop fueling by integer sale.

Screen touch

主要技术参数 Technical Specification

适应温度 Adapt temperature	-40°C~+50°C
环境温度适应性 Ambient temperature adaptability	-25°C ~ 55°C
相对湿度适应性 Relative humidity adaptation	30%~90%
电压 Voltage	AC220V±20%、AC380V±20%、AC110V±20%
电源适应能力 Power adaptability	AC220V(+10%,-15%), (50±1)Hz
大气压力 Atmospheric pressure	86kPa~106kPa
单次量程 Single range	(1-9900.00) L or RMB (as required)
累计量程 Accumulative range	(1-99999999.99) Lor RMB (as required)
频率 Frequency	(50±1)Hz, (60±1)Hz
单价设定范围 Unit price setting range	0~9999
密度预设范围 Density preset range	0.5000~0.6999
电磁阀关闭设定范围 Solenoid valve turn off setting range	0~0.99Liter
充气预设范围 Gas-filling preset range	0.3~9000升
计量单位 Unit Of Measurement	加气量 Air volume: L或kg Lite or kg
金额 Amount	元 RMB (as required)
单价 Unit Price	元/L RMB/Lite (as required)

液化石油气LPG加气机 LPG Dispenser

Welldone 汇洋能源

LPG灌装称 LPG Filling Scale



主要技术参数 Technical Specification

防护等级 Protection Grade	面板式:IP65 (panel type)
最大称重量 Max Weighing	150kg
准确度等级 Level Of Accuracy	OIMLIII级 class
工作温度 Working Temperature	-10~40℃
工作湿度 Humidity	10%~95%(不冷凝 non-condensing))
额定电压 Rated Voltage	24VDC
最大功率 Max Power	19.5W
液化气压力 Gas Pressure	1.0~1.6MPa
秤台台面尺寸 Weighing Platform Table Size	420×550mm
防爆标志 Proof Mark	Exd (ib) ib II BT4

液化石油气罐 Liquefied petroleum gas cylinder



液化石油气LPG加气机配件 LPG dispenser parts Welldone 汇洋能源

LPG流量计 LPG Flow Meter

机体材料 Material: 铸铁 Cast Iron

LPG 液化气流量计用于液化气加气机,采用不锈钢缸套,四活塞行程结构,进口内置止回阀,具有强度高,耐磨性好,计量精度高,使用寿命长.

LPG flow meter is in construction of stainless steel bush and four-piston positive displacement with check valve built in, with advantage of high reliability, good wearability, precise measure, and long life.



主要技术参数 Technical Specification

最大工作压力 Max.working Pressure	1.8MPa
流量范围 Flow Range	5-60L/min
每转排量 Discharge Rate Per Revolution	0.5L/R
最小可调量 Adjustable Minimum Volume	0.1%
精度 Accuracy	±0.5%
重复度 Repeatable Tolerance	+0.25%
包装尺寸 Dimension	32×27×36cm
净重 Net Weight	31kg
毛重 Gross Weight	35kg
包装 Package	1pc/CTN

LPG分离器 LPG Separator

内置止回阀、回气管路、过滤网. Check valve,filter,by pass pipe built in LPG separator



主要技术参数 Technical Specification

最大工作压力 Working Pressure	2.5Mpa
溢流压力 By Pass Pressure	4.0Mpa
过滤网精度 Strainer	0.08mm
包装尺寸 Dimension	54×38×36cm
净重 Net Weight	17.5kg
毛重 Gross Weight	23kg
包装 Package	1PC/CTN

LPG压力表 LPG Manometer

精度Accuracy: ±2.5% 量程Pressure: 0-4MPa



LPG 压力表LPG Manometer

LPG加气枪架 LPG Nozzle Boot




A type



B type

液化石油气LPG加气机配件 LPG dispenser parts 汇洋能源

LPG液化气差压阀 LPG Differential Valve



A type

B type

主要技术参数 Technical Specification

工作压力 Working Pressure	18Bar
压差 Pressure Difference	0.3Bar
流量 Flow Rate	50-60L/min
包装尺寸 Dimension	26×26×14.5cm
净重 Net Weight	27kg
毛重 Gross Weight	28kg
包装 Package	5pcs/carton

LPG防爆电磁阀 LPG Solenoid Valve



主要技术参数 Technical Specification

直径 Diameter	15mm 1/2"
连接方式 Connecting	Thread
流量 Flow Rate	5-50L/min
工作压力 Working Pressure	0-16bar
工作电压 Voltage	220V,50Hz
环境温度 Ambient Temperature	-20°C-65°C
包装尺寸 Dimension	39×36×29cm
净重 Net Weight	22.5kg
毛重 Gross Weight	31kg
包装 Package	20pcs/wooden case

LPG液化气拉断阀 LPG Breakaway



主要技术参数 Technical Specification

螺纹 Thread	M27×1.5
材料 Material	不锈钢 Stainless Steel
脱落拉力 Max.Pull Force	120Bar
流量 Flow Rate	5-50L/min

灌装枪 LPG Filling Nozzle

安装在LPG加气机上,用于给LPG气瓶充LPG的作用。
It installed on LPG dispenser, It can fill LPG to LPG cylinder
Material 材料: 不锈钢 stainless steel
气瓶阀尺寸 size of cylinder valve: 定制 as required



不锈钢双流量LPG电磁阀 SS Double LPG Solenoid Valve

Diameter 尺寸: 25mm 1"
Material 材料: SS304
Voltage 电压: DC12V, AC110V/220V
Working pressure 工作压力: 0-4.0MPa



液化石油气LPG加气机配件 LPG dispenser parts Welldone 汇洋能源

LPG加气枪 LPG Nozzle



A type



B type

主要技术参数 Technical Specification

进口 Inlet	BSPF/NPT3/4" or 1"
最大工作压力 Max Working Pressure	25Bar
断开时LPG的渗漏速度 LPG Discharge On Disconnect	4.3cc
温度 Temperature Range	-40℃~85℃
连接方式 Coupling Style	Italian Style
包装尺寸 Dimension	360×320×320mm
净重 Net Weight	20kg
毛重 Gross Weight	21kg
包装 Package	10PCS/CTN

LPG液化石油气软管 LPG Hose

使用范围 Usage range

用于液化石油气等。
Used in homely burning system ,LPG and so on .
工作压力Working pressure: 12 BAR
温度范围Temperature range: -35℃—90℃



产品结构 Product structure

内胶:黑色,表面光滑,丁腈复合橡胶 Inside rubber:Black,smooth surface,nitrile composed rubber
加强层:高强度复合丝 Strengthen layer:High powerful composed wire
品牌:根据客户需求 Brand:According to the customer demand
外胶:橙色,表面光滑,耐老化,耐油耐磨,丁腈复合橡胶
Outer rubber:Orange,smooth surface,aging proof,bear oil and wear,nitrile composed rubber

主要技术参数 Technical Specification

口径ID(mm)	内径ID(inch)	厚度WALL(mm)	工作压力WP(bar)	BP(bar)	Radius(mm)	Weight(kg/m)
5	3/16	3.0	12	60	18	0.13
6	1/4	3.6	12	60	20	0.15
8	5/16	3.5	12	60	27	0.20
10	3/8	3.5	12	60	33	0.26



主要技术参数 Technical Specification

进口 Inlet	BSPF/NPT3/4" or 1"
最大工作压力 Max Working Pressure	25Bar
断开时LPG的渗漏速度 LPG Discharge On Disconnect	4.3cc
温度 Temperature Range	-40°C~85°C
连接方式 Coupling Style	Italian Style
包装尺寸 Dimension	360×320×320mm
净重 Net Weight	20kg
毛重 Gross Weight	21kg
包装 Package	10PCS/CTN

LPG钢瓶集成阀 LPG Steel Cylinder Integration Valve

此产品安装于液化石油气钢瓶上, 主要用途为定量充装燃气、管路断裂自动保护、安全压力排放、液位显示、手动截止等, 产品具有外型美观、结构紧凑、不锈钢浮球不变形、不增重等优点.


This product is installed on the LPG steel cylinder for gas filling quantification, automatic pipe rupture protection, safety pressure relief, LPG-level display and manual cut-off. It features a nice appearance, compact structure, non-deforming stainless steel float and no weight gain. It's suitable for the gas system installation of engines on gasoline engine boosting bicycles, passenger cars, forklifts, airships, vessels, etc.



主要技术参数 Technical Specification

额定工作压力 Rated working pressure	≤2.2MPa
安全阀额定压力 Set-pressure of safety valve	钢瓶理论容积的80% 80% of the theoretical volume of the cylinder
充装容积 Filling volume	2.5MPa ±0.2MPa
适装钢瓶直径 Applicable cylinder diameter	180mm/250mm/280mm/314mm/400mm/450mm

LPG液化石油气叶片泵LYB-2000 LPG Vane Pump



LYB-2000 槽车叶片泵,用于传输液化气、氨水等,特别是用在高压差、超速转动、吸程低的恶劣工作环境下。
 LYB-2000 Vane Truck Pumps, for LPG,NH3 , is specially designed to perform in such severe operating conditions such as high differential pressure, pump over speeding, poor suction conditions.

主要技术参数 Technical Specification

进口 Inlet	NPT2"
出口 Outlet	NPT2"
最大转速 Max.Speed	800RPM
电机功率 Motor	7.5KW
温度范围 Temperature	-32℃~107℃
最大工作压力 Max.Working Pressure	28.6Bar
最大压差 Max.Differential Pressure	83.6Bar
内置溢流阀 Internal Relief Valve	Yes
包装尺寸 Dimension	54×38×37cm
净重 Net weight	41kg
毛重 Gross weight	50kg
包装 Package	1台/木箱 1Pc/wooden case

优点 Advantage

革命性的凸轮设计,真正消除气蚀现象,新凸轮、叶片材料和重型轴承的使用,增加了泵的使用寿命,单一机械密封设计,维护更换简单便捷大尺寸非金属推杆使泵可以高速旋转。
 Innovative cam design nearly eliminates cavitation. New materials in cam, blades and heavy-duty bearings prolong pump life. With a single mechanical seal, seal replacement and maintenance are easy. Large-diameter non-metallic pins fit higher pump speeds.

应用 Application

液化气和氨水的批量传输 LPG and NH3 bulk transfer
 加气站 Auto-fuel pumping
 液化气装罐 LPG cylinders

转速Speed(RPM)	压差Differential Pressure(Bar)	流量Flow Rate(L/min)	功率Power(KW)
800	3.4	323	2.3
	6.9	287	4.6
650	3.4	261	1.9
	6.9	227	3.8
500	3.4	189	1.4
	6.9	155	2.9

液化气泵
 YQB LPG Pump



YQB系列液化石油气泵,用于输送液化石油气、二甲醚等性质类似的挥发性液体及石油产品,尤其适用于液化石油气装卸车、钢瓶灌装、车间供料等。此泵为容积式叶片泵,结构先进,定子曲面由复合曲线构成,两端用机械密封,固定配合端面用“O”型密封圈,旋转配合部件采用金属配非金属,安全可靠、一机多用。

YQB series LPG pump are mainly used to transport various volatile liquids and petroleum products ,such as LPG, methyl ether, chloromethane, epoxyethane,propane, propylene, butadiene, isobutene, methanol and so on, especially used for LPG loading and unloading trucks, cylinder filling, and workshop feeding.The pump is positive displacement vane pump , its structure is advanced,the stator surface is composed of composite curves, mechanical seals are adopted at both ends, and the "O" sealing ring is used for each fixed mating face. All the rotating components are made of metal corresponding non-metal. It's safe ,reliable and multi-function .

型号Model:YQB ※-5型 YQB-液气泵5-升压范围—(进出口压差) ※-泵的额定流量
 Model meaning:YQB- LPG pump 5- step-up range (inlet and outlet pressure differential) ※-rated flow of pump


工作原理:本泵型式为容积式叶片泵,工作靠叶片离心滑动,流量与轴的转速有关,定子内曲面采用国内独创的复合曲线制成,定子与转子、挡板、叶片组成十个密封腔体,由于定子曲面是复合曲线,当转子转动时进口腔体积逐渐增大,并形成负压产生吸力,从而将油液吸入,当转子旋转一定角度后,容积截面逐渐减小,从而将油液压出,在吸油腔与压油腔之间有一封油块把吸油腔与压油腔隔开.叶片靠离心力和两挡板结构从而与定子内曲面紧密贴合,使泵在额定状态下正常工作.

Operational principle: The pump is positive displacement vane pump ,which depends on the centrifugal sliding of the vane. The flow is related to the shaft speed. The inner surface of the stator is made of the original composite curve. The stator is composed of ten sealed chamber with the rotor,the baffle and the vane. Because the stator surface is a compound curve, when the rotor is rotating,the volume of the chamber is gradually increased to form a negative pressure, suction is generated, so that the oil is sucked in.When the rotor rotates a certain angle, the volume decreases gradually, and the oil is hydraulic output. There is an oil block between the suction chamber and the pressure chamber to separate the suction chamber from the pressure chamber. The vane is tightly attached to the inner surface of the stator by centrifugal force and two baffle structures, so that the pump canwork normally under rated condition.

型号 Model	转速 Speed	流量 Flow	工作压力 Working Pressure	功率 Power	出入口尺寸 Size Of Inlet/outlet	温度范围 Temperature Range
YQB2-5	600 r.P.m	2m3/h	1.6MPa	1.5KW	1	+40 -40
YQB5-5	780 r.P.m	5m3/h		2.2KW	1.2	
YQB10-5	600 r.P.m	10m3/h	1.6MPa	5.5KW	2	
YQB15-5	780 r.P.m	15m3/h				
YQB115-5A	780 r.P.m	15m3/h	1.6MPa	4KW	2	
YQB10-5A	600 r.P.m	10m3/h				
YQB25-5	600 r.P.m	25m3/h	1.6MPa	11KW	3	
YQB35-5	780 r.P.m	35m3/h				
YQB50-5	600 r.P.m	50m3/h	1.6MPa	15KW	4	
YQB60-5	780 r.P.m	60m3/h	1.6MPa	15KW	4	
YQB80-5	780 r.P.m	80m3/h	1.6MPa	18.5KW	4	

LPG

LWB-150 LPG Turbine Pump



概述 Overview

LWB-150 涡轮泵在地上或地下气罐的高压差时使用

LWB-150 LPG Turbine Pump, for high differential pressure application using, for underground and aboveground tank application.

优点 Advantage

经济高效的潜泵替代泵;

满足多种LPG加气需求, 高压差时, 无论地上液化气罐, 还是地下液化气罐, 可以为双枪加气机大流量加气;

连续高强度使用设计, 使用起来简单经济;

A cost effective alternative to submersible designs.

Meeting multiple demands for LPG application. Whether a low or high flow rate with a high differential pressure, by underground and aboveground tank application, LWB-150 pump is an idea pump for two dual hose LPG dispensers. Continuous duty design.

Serviceability is simple and cost effective.

应用 Application


经济高效的潜泵替代泵; 加气机加气; 装罐; 液化气蒸气回收; 批量输送;

Autogas Dispensing; Cylinder Filling; Vaporizer Feed; Bulk Transfer

主要技术参数 Technical Specification

型号 Model	泵头 Pump only	泵总成 Pump with motor
进口 Inlet	1.5"	
出口 Outlet	1"	
转速 Speed	60Hz, 3450RPM or 50Hz 2880RPM	
电机功率 Motor	5.5kw	
温度范围 Temperature	-32°C~107°C	
最大工作压力 Max. Working Pressure	27.6Bar	
最大压差 Max. Differential Pressure	17.2Bar	
包装尺寸 Dimension	43×33×42cm	95×45×60cm
净重 Net weight	29kg	133kg
毛重 Gross weight	35kg	153kg
包装 Package	1台/木箱 1Pc/wooden case	

LPG液化气多级泵
 DB-65 LPG Side Channel Multistage Pump



概述 Overview

DB-65 液化气多级泵是离心式侧流道泵, 采用了水平结构, 共6级, 轴采用机械密封, 无需冷却。该泵用于传输液化气, 特别是高压力差、低气蚀余量和气体含量高达50%的液体, 例如从地下罐中泵液化气。
 The DB-65 multistage pump, centrifugal and side channel, is designed with 6 stages, having a horizontal configuration, Shaft sealing by mechanical seal without cooling, for handling LPG (liquid gas), the liquids involving high-differential pressure, low NPSH conditions and aerated liquids up to 50% gas, such as pumping from underground tanks.

应用 Application

装瓶,从地下罐中泵液化气,油罐车,槽车装车、卸车, 液化气蒸气回收。
 LPG Cylinder Filling;Pumping LPG From Underground Storage ;Bulk Filling Operations ;Loading/Unloading Of Bulk Trucks And Transport Trailers; Vaporizer Feed Pumps.

主要技术参数 Technical Specification

型号Model	泵总成 DB-65 with motor		泵头 DB-65 with out motor
旋转方向 Direction of rotation	面对泵的驱动轴末端逆时针旋转Anti-clockwise facing the end of the pump drive shaft		
最大工作压力 Max.working pressure	在120°C时40公斤 40bars at 120°C		
转速 Speed	1450RPM		
电机功率 Motor	380V,50HZ,4KW/220V,50HZ,4KW		
环境温度 Ambient temperature	20°C~ +40°C		
级数 Number of stages	6级 6stage		
连接法兰 Max.differential pressure	DIN250 1, PN40		
轴承 Bearings	泵端滑动轴承、驱动端滚珠轴承 sleeve bearing at the pump end, ball bearing at the drive end.		
润滑 Lubrication	泵端的滑动轴承由泵的液体润滑、驱动端的滚珠轴承自润滑 Plain bearing at the pump end lubricated by the pumped product,ball bearing at the drive end lubricated for life.		
包装尺寸 Dimension	112×42×57cm		110×48×45cm
净重 Net weight	136kg		64kg
毛重 Gross weight	148kg		78kg
包装 Package	1台/木箱 1Pc/wooden case		

ABOUT US

We are the gas station equipment supplier in Hydrogen Energy, Liquid Natural Gas, Compressed Natural Gas, Liquid Petrol Gas, Fuel, Adblue, EV charger, Home Energy Storage, Industrial Energy Storage area. If you are doing the same range business, if you are interested in new energy, welcome you to visit us!

We have many certificates like ISO, CE, ATEX, PED, TUV, PEI, CPA, CMA, Explosion proof certificates and soon. We have our own Patent and copyrights.

Wish our products, our service can give you a strong impression.

Well Quality We Done! Well Service We Done! Well Price We Done!

We are Welldone Group!

HONOR



Fuel Dispenser ATEX



LNG Dispenser ATEX



Mobile Gas Station ATEX



LNG Dispenser PED



Submersible Turbine Pump ATEX




Junction Box ATEX



LPG dispenser ATEX-D



LPG dispenser ATEX-B



Mass Meter ATEX



Positive Displacement Meter CE



Mobile Gas Station CE



Adblue Dispenser CE



LNG Dispenser CE



CNG Dispenser CE



LPG Dispenser CE




Fuel Dispenser CE



EV Charger TUV



PEI



Radiographic Examination Report



CNG Dispenser Explosion Proof CMA



LNG Dispenser Explosion Proof CMA



PQR Test Report



Patent Certificates For Management System



Factory ISO



LNG Dispenser CPA



CNG Dispenser CPA



Welldone Copyrights



E-BOOK